



Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 4/21/2021 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Reveal H.D. Non Ammoniated Stripper
Product code : 198-9815

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

RMAC Supplies Co.
1700 Palisade Avenue
Teaneck, NJ 07666
T (718) 624-5157

1.4. Emergency telephone number

Emergency number : (800) 535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Potassium Hydroxide, 45%≤conc<50%, aqueous solutions (Cleaning Agent, pH Adjuster)	CAS-No.: 1310-58-3	1 – 5	Acute Tox. 3 (Oral), H301 Skin Corr. 1, H314

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
2-aminoethanol (Additive, Corrosion Inhibitor, Emulsifier)	CAS-No.: 141-43-5	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314
butyl glycoether (Solvent)	CAS-No.: 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

No additional information available

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

No additional information available

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

No additional information available

7.2. Conditions for safe storage, including any incompatibilities

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Reveal H.D. Non Ammoniated Stripper

No additional information available

butyl glycoether (111-76-2)

USA - ACGIH - Occupational Exposure Limits

Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Remark (ACGIH)	Eye & URT irr

USA - OSHA - Occupational Exposure Limits

Local name	2-Butoxyethanol
OSHA PEL (TWA) [1]	240 mg/m ³
OSHA PEL (TWA) [2]	50 ppm

2-aminoethanol (141-43-5)

USA - ACGIH - Occupational Exposure Limits

Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm
Remark (ACGIH)	Eye & skin irr

USA - OSHA - Occupational Exposure Limits

Local name	Ethanolamine
OSHA PEL (TWA) [1]	6 mg/m ³
OSHA PEL (TWA) [2]	3 ppm

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

USA - ACGIH - Occupational Exposure Limits

Local name	Potassium hydroxide
Remark (ACGIH)	URT, eye, & skin irr

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

butyl glycoether (111-76-2)

LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450 – 486 ppm/4h 450-486,Rat
ATE US (dermal)	435 mg/kg body weight
ATE US (gases)	450 ppmV/4h
ATE US (vapors)	2.17 mg/l/4h
ATE US (dust, mist)	2.17 mg/l/4h

2-aminoethanol (141-43-5)

LD50 oral rat	1515 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	2504 mg/kg body weight (Equivalent or similar to OECD 402, 24 week(s), Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	1515 mg/kg body weight
ATE US (dermal)	2504 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

LD50 oral rat	273 mg/kg (Rat, Oral)
ATE US (oral)	273 mg/kg body weight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

SECTION 12: Ecological information

12.1. Toxicity

2-aminoethanol (141-43-5)

LC50 - Fish [1]	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Daphnia [1]	65 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

LC50 - Fish [1]	80 mg/l (96 h, Gambusia affinis, Pure substance)
-----------------	--

12.2. Persistence and degradability

butyl glycolether (111-76-2)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31

2-aminoethanol (141-43-5)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance
BOD (% of ThOD)	0.32

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

butyl glycoether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2-aminoethanol (141-43-5)	
BCF - Other aquatic organisms [1]	2.3 – 9.2 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

butyl glycoether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
2-aminoethanol (141-43-5)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	1.16 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Ecology - soil	No (test)data on mobility of the components available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

14.1. UN number

DOT NA no.	: UN1813
UN-No. (TDG)	: Not applicable
UN-No. (IMDG)	: 1813
UN-No. (IATA)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Potassium hydroxide, solid
Proper Shipping Name (TDG)	: Not applicable
Proper Shipping Name (IMDG)	: POTASSIUM HYDROXIDE, SOLID
Proper Shipping Name (IATA)	: Not applicable

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : Not applicable
Packing group (IMDG) : II
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1813

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2). IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle. IP4 - Flexible, fiberboard or wooden IBCs must be sift-proof and water-resistant or be fitted with a sift-proof and water-resistant liner. T3 - 2.65 178.274(d)(2) Normal..... 178.275(d)(2) TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 212
DOT Packaging Bulk (49 CFR 173.xxx)	: 240
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 15 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 50 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
TDG	
Emergency Response Guide (ERG) Number	: 154
IMDG	
Limited quantities (IMDG)	: 1 kg

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

butyl glycoether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-aminoethanol (141-43-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Reveal H.D. Non Ammoniated Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ

1000 lb

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product